




TRANSHOW SCREW FACTORY

GAOYANG RD, ZHOUMAN VILLAGE, JIANGSHAN TOWN
 YINZHOU DISTRICT, NINGBO CITY, 315100 CHINA
 Tel: +86-574-8736.7873 Fax: +86-574-8736.4349
www.transhow.net Email:transhow@transhow.net

Self Tapping Screw Thread Type U

Round Head Drive Screw



Nominal Screw Size	Number Of Thread Starts	D		A		H		P		Recommended Hole Size	
		Outside Diameter		Head Diameter		Head Height		Pilot Diameter		Drill Size No.	Hole Diameter
		Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.		
0	6	0.060	0.057	0.099	0.090	0.034	0.026	0.049	0.046	55	0.052
0	6	0.075	0.072	0.127	0.118	0.049	0.041	0.063	0.060	51	0.067
2	8	0.100	0.097	0.162	0.146	0.069	0.059	0.083	0.080	44	0.086
4	7	0.116	0.112	0.211	0.193	0.086	0.075	0.096	0.092	37	0.104
6	7	0.140	0.136	0.260	0.240	0.103	0.091	0.116	0.112	31	0.120
7	8	0.154	0.150	0.285	0.264	0.111	0.099	0.126	0.122	29	0.136
8	8	0.167	0.162	0.309	0.287	0.120	0.107	0.136	0.132	27	0.144
10	8	0.182	0.177	0.359	0.334	0.137	0.123	0.150	0.146	20	0.161
12	8	0.212	0.206	0.408	0.382	0.153	0.139	0.177	0.173	11	0.191
14	9	0.242	0.236	0.457	0.429	0.170	0.155	0.202	0.198	2	0.221
L	Nominal Screw Length	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1 in. and over	
S	Pilot	0.05	0.047	0.05	0.05	0.06	0.06	0.08	0.08	0.125	