





TRANSHOW SCREW FACTORY

GAOYANG RD, ZHOUEAN VILLAGE, JIANGSHAN TOWN
 YINZHOU DISTRICT, NINGBO CITY, 315100 CHINA
 Tel: +86-574-8736.7873 Fax: +86-574-8736.4349
 www.transhow.net Email:transhow@transhow.net

Slotted Drive



Phillips Drive



Truss Head Dimensions for Self Tapping Screws And Self Drilling Screws, Machine Screws

Nominal Size	A		H		J		T		M		G	N	Phillips Driver Size
	Head Diameter		Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess				
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	
4	0.257	0.241	0.069	0.059	—	—	—	—	0.112	0.099	0.069	0.017	1
6	0.321	0.303	0.086	0.074	0.048	0.039	0.050	0.037	0.158	0.145	0.084	0.027	2
8	0.384	0.364	0.102	0.088	0.054	0.045	0.058	0.045	0.173	0.160	0.099	0.029	2
10	0.448	0.425	0.118	0.103	0.060	0.050	0.068	0.053	0.188	0.175	0.115	0.030	2
1/4"	0.573	0.546	0.150	0.133	0.075	0.064	0.087	0.070	0.263	0.250	0.143	0.033	3
5/16"	0.698	0.666	0.183	0.162	0.084	0.072	0.106	0.085	0.352	0.339	0.193	0.059	4
3/8"	0.823	0.787	0.215	0.191	0.094	0.081	0.124	0.100			—	—	

Note: these dimensions are in inch standard as per ANSI/ASME standard. For guide only. All screws could be customized